

## BOGE S-4 series

Designed to take the lead



### TECHNICAL DATA

BOGE type	Max. pressure bar	Effective free air delivery m <sup>3</sup> /min	Rated output		Dimensions W x D x H (mm)	Compressed air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
			Main drive kW	Fan motor kW				
S 56-4 LF(D)	7.5	2.8 - 10.9	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 LF(D)	10	2.5 - 9.0	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 LF(D)	13	3.5 - 7.2	55	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 56-4 L(D)	7.5	10.1	55	2.2	2330 (2780) x 1420 x 1990	DN 65	2070 (2310)	2090 (2330)
S 76-4 (D)	7.5	14.1	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 (D)	10	12.5	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 (D)	13	10.4	75	2.2	2330 (2780) x 1420 x 1990	DN 65	2160 (2420)	2180 (2440)
S 76-4 LF(D)	7.5	2.9 - 14.4	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 76-4 LF(D)	10	2.8 - 12.3	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 76-4 LF(D)	13	2.6 - 10.4	75	2.2	2380 (2780) x 1420 x 1990	DN 65	2150 (2410)	2170 (2430)
S 90-4 (D)	7.5	16.5	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 (D)	10	15.0	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 (D)	13	12.6	90	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 90-4 LF(D)	7.5	2.9 - 16.6	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 90-4 LF(D)	10	2.8 - 14.7	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 90-4 LF(D)	13	2.7 - 12.8	90	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 (D)	10	17.1	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 110-4 (D)	13	15.2	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2260 (2520)	2280 (2540)
S 110-4 LF(D)	7.5	5.8 - 19.2	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 LF(D)	10	2.8 - 16.3	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 LF(D)	13	2.8 - 14.4	110	3.0	2380 (2780) x 1420 x 1990	DN 65	2250 (2510)	2270 (2530)
S 110-4 L(D)	7.5	19.3	110	3.0	2330 (2780) x 1420 x 1990	DN 65	2170 (2430)	2190 (2450)

## BOGE S-4 series

Designed to take the lead



### TECHNICAL DATA

BOGE type	Max. pressure bar	Effective free air delivery m <sup>3</sup> /min	Rated output		Dimensions W x D x H (mm)	Compressed air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
			Main drive kW	Fan motor kW				
S 91-4	7.5	17.4	90	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 91-4	10	15.5	90	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 91-4 LF	7.5	5.4 - 18.1	90	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 91-4 LF	10	5.3 - 16.2	90	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4	7.5	20.5	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4	10	17.5	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4	13	14.4	110	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	7.5	5.5 - 21.1	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	10	5.3 - 18.5	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 LF	13	4.9 - 14.4	110	3.0	2980 x 1620 x 1990	DN 80	3550	3600
S 111-4 L	7.5	20.5	110	3.0	2930 x 1620 x 1990	DN 80	3450	3500
S 132-4	7.5	24.1	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4	10	21.7	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4	13	17.2	132	3.0	2930 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	7.5	5.5 - 25.0	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	10	5.3 - 21.8	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 LF	13	5.0 - 17.9	132	3.0	2980 x 1620 x 1990	DN 80	3650	3700
S 132-4 L	10	20.2	132	3.0	2930 x 1620 x 1990	DN 80	3550	3600
S 160-4	7.5	28.1	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4	10	25.0	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4	13	21.2	160	5.5	2930 x 1620 x 1990	DN 80	3700	3750
S 160-4 LF	7.5	5.5 - 27.7	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 LF	10	5.3 - 25.1	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 LF	13	5.0 - 21.2	160	5.5	2980 x 1620 x 1990	DN 80	3750	3800
S 160-4 L	13	19.3	160	5.5	2930 x 1620 x 1990	DN 80	3600	3650